


# MAX-E2/841® VERTICAL ROUND BODY SOLID SHAFT NORMAL/MEDIUM THRUST with "P" BASE - LOW VOLTAGE



AEUH8BDP, NEMA PREMIUM, ROUND BODY [HBV\_P]

Effective 07-08-18  
Supersedes 03-24-17



## APPLICATIONS:

- Centrifugal Pumps
- Pulp and Paper
- Petro-Chemical
- Water/Wastewater

## FEATURES:

- Output Range: 15 - 100 HP
- Speed: 3600, 1800 & 1200 RPM
- Enclosure: Totally Enclosed Fan Cooled (IP56)
- Voltage: 460V Only<sup>(1,4)</sup>
- Three Phase, 60 Hz, 1.15 Service Factor (Continuous); 50 Hz, 1.0 Service Factor (Continuous)
- CSA Certified for Class I, Div. 2, Groups B, C, D - Temp Code T3 Minimum
- Meets or Exceeds IEEE 841 Standards
- Extended Warranty - 60 Months from Date of Manufacture
- Class F Insulation
- Class B Temperature Rise
- NEMA Design B Torques as a Minimum; Various Ratings also Meet Design C
- Cast Iron Frame, End Brackets, Fan Cover, Drip Cover and Main Conduit Box
- Grounding Terminal Inside Main Conduit Box with additional Foot Grounding Provision
- Oversized Main Conduit Box Rotatable in 90 Degree Increments - F1 Mounted
- Designed for 50°C Ambient Temperature<sup>(2)</sup>
- Designed for 3300 ft. Elevation<sup>(3)</sup>
- Bi-Directional Rotation
- 1045 Carbon Steel Shaft
- Aluminum Die Cast Squirrel Cage Rotor Construction
- Paint System: 2 Part Epoxy
- Paint Color: Blue - Munsell 5PB 3/8
- Guide Bearings: 250HP - 400HP Frames are Single Shielded
- Thrust Bearings: 250HP - 405HP Frames are Re-Greasable Angular Contact with Mobil Polyrex™ EM
- Automatic Grease Discharge Fittings
- Cast Iron Inner and Outer Bearing Caps for all frames
- VBXX INPRO™ Seals Installed on Both Ends
- Stainless Steel Nameplate and Hardware
- Stainless Steel Automatic Breather Drain (Located at both End Brackets for Vertical Mounts)
- New Dual Column Design Nameplate as Standard (60/50 Hz)
- Suitable for Inverter Use per NEMA MG-1.4.4.2, Part 31.<sup>(5,6)</sup>
- Inverter Duty Speed Range: 20:1 Variable Torque, 10:1 Constant Torque
- Motors are U.L. Recognized, CSA Approved
- 3 Leads Only
- Vibration Not to Exceed 0.08 Inches Per Second
- Noise Level Not to Exceed 85 dB(A) at 1 Meter Unloaded
- NEMA Type P Base

## EXTRAS/ OPTIONS:

Please refer to the modifications document for common modifications that can be performed.

## Notes:

- (1) 575V motors available.
- (2) Consult a Stock Product Application Specialist for suitability in higher ambient environments.
- (3) Consult a Stock Product Application Specialist for suitability at higher elevations.
- (4) Motors 7.5 HP & up are suitable for wye/delta starting.
- (5) Motor service factor is 1.0 when operated on a VFD.
- (6) Precautions should be taken to eliminate or reduce shaft currents that may be imposed on the motor by the VFD as stated per NEMA MG-1.
- (7) HP Shaft is same as VP shaft dimensions per NEMA MG-1.