CONTROLS PRODUCTS



- V/Hz with Auto-Torque Boost or Sensorless Vector
- Built-in Modbus and BACnet Protocols

- Din Rail Mountable (with Mounting Kit)



E510 COMPACT INVERTER

- V/Hz, Sensorless Vector, Permanent Magnet Sensorless Vector
- Conformal PCB Coating
- PLC Functionality
- 5 Digit LED Removable Keypad with Speed POT
- Built-in Dynamic Braking Transistor for Ratings up to 25 HP
- Built-in Modbus & BACnet
- Removable Keypad for Remote Mounting
- NEMA 1 Conduit Kit Included as Standard (Frame 1-4)



A510 HEAVY DUTY INVERTER

- 1 400 HP (CT & VT), 230/ 460/ 575-690V
- V/Hz, Sensor Vector Closed Loop, Sensorless Vector, Permanent Magnet Sensor Vector, Permanent Magnet Sensorless Vector
- LCD Keypad with Copy Capabilities
- Extensive Diagnostics and Monitoring PLC Functionality
- Advanced Regeneration Load Handling
- Wide Range of Applications

LOW VOLTAGE SOFT STARTER

- 10 1000 HP, 208 575V
- Crusher Duty Panels Bypass with ATL Start
- Adaptive Control
- Door Mounted LCD Keypad
- Monitor, Program, and Troubleshoot Copy Capabilities
- Custom Engineered Packages
- Supplied as NEMA 1, NEMA 3R, or Chassis Configuration



- PID Capabilities with Sleep Mode, Engineering Units, Diagnostic Master/ Follower Controls
- V/Hz, Sensorless Vector, Permanent Magnet Sensorless Vector
- Standard LCD Keypad with Real-time Clock and Copy Capabilities PLC Functionality
- Built-in Modbus, Metasys, or BACnet Protocols



E510 NEMA 4/4X/12 - INDOOR USE ONLY

- 1/2 25 HP, 230/ 460V
- V/Hz or Sensorless Vector Control
- Integral Disconnect Switch Included on N4FS Models
- PLC Functionality
- 5 Digit LED Display
- Built-in Dynamic Braking Transistor
- PID Control



EQ7 MULTI-PURPOSE INVERTER

- 1 1000 HP (VT), 230/ 460V
- 1 900 HP (CT), 230/ 460V V/F Dynamic Torque, Sensorless, Sensor, and PI Vector
- Robust Design and Wide Capabilities
- LED/ LCD Keypad with Extensive Monitoring, Copy, and Diagnostic Capabilities
- Conformal Coating and Tin-Plated DC Bus
- UL Approved Single Phase Input Operation



MEDIUM VOLTAGE SOFT STARTER

- 500 6000 HP, 2300 7200V
- Current, Torque, HP, or Voltage Modes of Start Up
- Kick Start Capabilities



- Heavy Duty with Across the Line (ATL) Rated Bypass Can Operate as a Soft Starter or ATL starter

- LCD Keypad with Copy Capabilities on Door as Standard

tional Cabinets with Fused Disconnects or Circuit Breaker

- NEMA 1, 12, 3R are Standard (NEMA 4 by Request) 208, 230, and 460V Standard (Packages at 380, 415, 575,
- and 600V Available on Request) Wall or Floor Mounting Door; Mounted Control Devices
- Packaged Inverters with Bypass 2 or 3 Contactor Bypass
- Circuit Breaker or Fused Disconnect
- Input/ Output Reactors and DV/ DT Filters
- All Features as Shown with Optional Cabinets

M+I PACKAGES



Additional Discount When Purchasing Matching Motor and Inverter as a Set

- Premium Efficient Motors and Inverter Combination Packages Packages Developed for Both Constant or Variable Torque Applications
- Motors 900 through 3600RPM; 230,460V
- Rolled Steel and Cast Iron ODP: 143T through 5009E
- Max-E1® Type AEHE, AEHH8N through 800 HP nverters - 230VAC: 1-125 HP; 460VAC: 1-800 HP
- EQ7 or A510 Inverters for Constant Torque Application
- EQ7 or F510 Inverters for Variable Torque Applications
- 5 Year Warranty Valid on All Combination Packages

SERVICE

Sepair and Refurbish all Brands of Large Motors

- Expert Field Service and Technical Assistance Redesign and Uprate of Westinghouse and TWMC Motors
- Repairs Using OEM Materials and Processes for Longer Life Engineered Solutions to Large Motor Problems
- ligh Voltage (to 13.8kV) Repairs with Global VPI Dual Frequency Load Testing
- Finder's Fee Incentives Available
- Service Division Hotline: 888-754-5006



CONTROL WHEELS

Convert Other OEM Unsupported Control Wheels to a TWMC Design

Renewal Parts for Over 500,000 Westinghouse and

DC Armatures, Field Frames, and Commutators

Replacement and Improved Design Cooling Packages

Engineered Replacement Components

AC Rotors and Stators

Field Pole Assemblies

(WPII, TEWAC, and TEAAC)

VersaBridge® MVD Components

TECO-Westinghouse Form Wound/ High Voltage Motors

Built in Pittsburgh, PA; Buffalo, NY; and Round Rock, TX.

- On-Site Troubleshooting, Repairs, and Rebuilds In Stock Renewal Parts
- Finder's Fee Incentives Available



EXCITER CONTROL PANELS

OUICK TURN REWINDS

with Deliveries Ranging from 17 - 27 days

Thermalastic® Epoxy Insulation System

All Manufactures' Motors

In-House Coil Manufacturing

ISO 9001 Quality System

Finder's Fee Incentives Available

Full Rush Overtime Medium and High Voltage Rewinds Performed

Replace Outdated Analog Controls with a Modern Digital System Using the Same Panel Space

- Superior Control and Accuracy of Voltage, VAR, and Power Factor Regulation
- Enhanced System Response
- Advanced Motor Protection
- Reliable System Operation
- Finder's Fee Incentives Available



ROTOR BALANCE SERVICES

- High Speed Balancing for Rotors Up to 110K LBS.
- Identify Critical Speeds & Optimal Weight Planes Eliminate Unbalance from Ramp Up through Rated Speed
- Verify Mechanical Integrity of the Rotor Assembly
- Ideal Candidates Include: Rewound Rotors, Disassembled/ Rebuilt Rotors, Flexible and/or Long Slender Rotors, Repairs Resulting in Rotational Center Changes, & Rotors with Vibration Problems Due to Rubbing, Cracking, or Thermal Instability

TECO-Westinghouse is a leading manufacturer of electric motors and inverters. We offer a full line of induction, synchronous, and DC motors & generators available from 1/4 HP to 100,000 HP, as well as a wide variety of low and medium voltage inverters (MV inverters) and motor controls. Most recently, we introduced a line of Motor Health Management accessories, portable and permanent, that allows users to manage data on temperature and vibration analysis. We can also test MV inverters and motors as a package in our Round Rock, Texas factory. Additionally, we supply switchgear, system studies, and aftermarket services such as engineering studies, genuine Westinghouse renewal parts, and large motor and inverter repairs.



TECO W Westinghouse

PRODUCTS OVERVIEW



MOTORS | CONTROLS | SERVICE ENGINEERED SYSTEMS SOLUTIONS

STOCK MOTOR PRODUCTS



FARM DUTY - TEFC

- 1/3 10 HP: 1800 RPM 115/230V through 2 HP, 230V for 3 HP and Above
- 1.15 Service Factor, Continuous Duty
- Manual Reset Overload Protection

- ODP 1/4 3 HP: 3600, 1800 RPM TEFC 1/4 - 10 HP: 3600, 1800 RPM
- EPACT: TEFC 3 10 HP: 3600, 1800 RPM



ROLLED STEEL MOTORS 1/4 - 40 HP (0DP): 3600, 1800, 1200 RPM

- 1/4 10 HP (TEFC): 3600, 1800, 1200 RPM
- 230/ 460V
- NEMA Premium Efficiency with 60/50Hz Nameplate
- Wound with Inverter Duty Wire
- 1.15 Service Factor, Continuous Duty
- Multiple Mountings for 56 and 140T Frames; Dual Mountings on 180T and Larger
- UL Approved Fire Pump / Safety Red Paint Option Available



ODP CAST IRON MOTORS

- 1 800 HP: 3600, 1800, 1200 RPM
- 230/ 460V through 125 HP, 460V for 150 HP and Larger
- Also Available in 575V
- Suitable for Inverter Duty with 20:1 Variable Torque and 10:1 Constant Torque Speed Ranges
- All Cast Iron Construction
- UL Approved for Fire Pump Applications
- C & D Flanges Available
- UL Approved Fire Pump / Safety Red Paint Option Available



MAX-PE™

- 1 200 HP: 3600, 1800, 1200 RPM
- Dual Rated for Both 230/460V 60Hz or 190/380V 50Hz
- Meets or Exceeds NEMA Premium Efficiency Levels
- Cast Iron Frame and End Brackets
- Rolled Steel Terminal Box and Fan Cover
- UL Recognized, CSA Certified and CE Marked

Footed C-Face and Round Body C-Face Stocked up to 200 HP

MAX-E1[®]

- 3/4 800 HP: 3600, 1800, 1200, 900 RPM
- NEMA Premium Efficiency, 500 HP and Below
- 230/ 460V through 125 HP, 460V for 150 HP and Larger Also available in 575V
- CSA and UL Approved for Inverter Duty per NEMA MG-1, Part 33
- CSA Certified for Class I, Div 2, Groups B, C & D Class II, Div 2, Group F, G 440 Frames and Larger





MAX-F2/841 1 - 500 HP: 3600, 1800, 1200, 900 RPM

- Meets or Exceeds IEEE 841 Standards INPROTM Seals - VRXX
- All Cast Iron Construction
- CSA Certified for Class I, Div 2, Groups B, C & D Class II, Div 2, Group F, G 440 Frames and Larger
- CSA and UL Approved for Inverter Duty per NEMA MG-1, Part 33

EXPLOSION PROOF (Division 1, Zone 1)

Footed C-Face and Round Body C-Face Available

- 1 400 HP: 3600, 1800, 1200, 900 RPM
- Class I, Group D, Class II Group E, F, & G, T3B
- Class I, Group C & D, Class II E, F &G, T3B for 256 frame and below
- UL Approved for Inverter Duty
- Footed C-Face and Round Body C-Face Stocked up to 100 HP

- High Torque Crusher Motors
- 20 150 HP at 230/ 460V; 460V above 150 HP
- 100 900 HP at 2300/ 4160V
- TEFC (IP55)
- NEMA Design C: 20 200 HP; (Locked Rotor Torque 200% FLT NEMA Design A: 250 HP & Up; (Locked Rotor Torque 200% FLT)
- CSA Certified for Class I, Div 2, Groups B, C & D, T3 Class II, Div 2, Group F & G, T3, 440 Frame and Above
- High Strength Steel, AISI 4140, Shaft Material
- Suitable for Vertical Mounting for Vertical Impact Crushers



GLOBAL SERIES® MEDIUM VOLTAGE

- 100 1000 HP (WPI): 3600,1800, 1200, 900 RPM 100 - 2000 HP (TEFC): 3600, 1800, 1200, 900 RPM
- 2300/ 4160V Dual Voltage
- Vacuum Pressure Impregnated Form Wound Coils 120V Space Heater and 100 0hm (Pt) Winding RTD's 2/ Phase
- TEFC Design Meets the NEMA Premium Standards



CLOSED COUPLED PUMP MOTORS (JM/JP) 1 - 50 HP

- 3600, 1800, 1200 RPM
- CE Marked
- Meets NEMA Premium Efficiency Requirements
- TEFC Motors have Cast Iron Frames ODP Motors have Rolled Steel Frames
- UL Approved for Fire Pump Application

OIL WELL PUMP MOTORS

- 125 HP (0DP): 1200 RPM
- 75 100 HP (TEFC): 1200 RPM
- ODP: 230/460V with Rodent Screen
- TEFC: 230/460V
- NEMA Design D. High Slip (Min. 5%)
- Standard with Klixon Temperature Limiting Device All Cast Iron Construction



STAINLESS STEEL WASHDOWN MOTORS

- 3/4 10 HP: 3600, 1800 & 1200 RPM
- TEFC /TENV (IP66)
- All Stainless Steel Construction
- All Motors Come with a C-Face Kit
- UL Recognized, CSA Certified and CE Marked
- F1/F3 Mounting Available



MAX-VH/VHP™/ MAX-VS/VSP™

- 7.5 800 HP: 1800, 1200 RPM
- Vertical Hollow and Solid Shaft, High Thrust Motors
- WPI/TEFC Enclosures Standard with Ball Type Non-Reversing Ratchet
- Multiple Coupling, Bases & Steady Bushing Options
- Wound with Inverter Duty Wire
- Oversized Angular Contact or Spherical Thrust Bearing
- UL Approved Fire Pump / Safety Red Paint Option Available



MAX-PM™ MOTORS 1/2 - 30 HP (TEFC): 3600, 1800, 1200 RPM

- 230/460 V
- 1.0 Service Factor, Continuous Duty

7.5 - 30 HP: 3600, 1800 RPM

- NEMA Frames F1/F2 Interchangeable
- IE4 Efficiency Level

IE5 SYNCHRONOUS RELUCTANCE MOTORS

- Used with A510 Advanced Inverter


ENGINEERED PRODUCTS



- 250 30,000 HP AC Induction Motors
- Thermalastic® Epoxy Insulation System Rugged Thru-Bolt Construction and End Rings
- Copper or Copper Alloy Rotor Bars
- Anti-Friction or Spherically-Seated, Self-Aligning Split-Sleeve Bearings
- High Efficiency Designs for Reduced Life-Cycle Costs API 541, PAM, and Marine Duty Designs Available
- Horizontal and Vertical Configurations

SYNCHRONOUS MOTORS


- 1000 100,000 HP
- Anti-Friction or Spherically-Seated, Self-Aligning, Split-Sleeve Bearings
- Brush or Brushless Excitation Thermalastic® Epoxy Insulation System
- High-Speed and Slow-Speed Designs Available
- VFD Applications Available Special Mill and Marine Duty Designs Available





WOUND ROTOR MOTORS

- Available from 25 20,000 HP
- Continuously Rated Slip Rings and Brushgear
- Heavy-Duty Rotor Construction for Dependable Service Thermalastic® Epoxy Insulation System
- Advanced Bearing System for Reliable Performance
- Rugged Frame Construction for Strength and Reliability





VERSABRIDGE

1000 - 40,000 HP; 2300 - 13,800V

- Scalable Modular Power Electronics Building Blocks NEMA 1 or NEMA 3R
- Advanced 2 Phase Liquid Cooling
- Water or Considerable HVAC Not Required

User Serviceable


- Fuseless & Filterless
- Patented Universal Design Proven Topology

Sealed Power Cubes

Film Caps (Long Life) Standard Components



Medium Voltage Inverter





2-phase coolii 2.3-15,V, 1-40kH

Patented, UL-list







Motors



Custom PLC logic a

100k HI



Proiect

PLC & HMI

Interfaces

Complete Provider

ENGINEERED SYSTEMS SOLUTIONS

TECO-Westinghouse is in a unique position of being able to provide quality motors,

generators, drives, and power solutions, all from our factory headquarters in Round

Rock, Texas. This capability, combined with our global manufacturing resources,

uniquely positions us to serve our customers' needs with any application and in any

industry. From standalone products such as our Versabridge® MVD and Modular Heat

Recovery System to full-scale system solutions involving Microgrid infrastructure,

TWMC also offers power solutions up to 15 kV and 40+ MVA. These solutions can be

integrated into existing infrastructure or built from the ground up at a new site. Using

TWMC as a turnkey system supplier allows the customer to mitigate risk, simplify the

Drives

TWMC offers custom design engineered systems of all scopes and scales.

contracts and logistics, and allows for improved deliveries and prices.



Electrical

Buildings

(E-House)

System

Studies

ETAP,





id cost whei





hort circuit, device ttings, arc flash.



- Anti-friction or Spherically-Seated, Self-Aligning,
- Split-Sleeve Bearings
- Air Filters and Differential Pressure Switch Included
- Ratings up to 35,000 HP for the Metals, Mining, Marine Special Insulation Coatings to Maintain High Insulation
- Minimal Maintenance
- Heavy-Duty Stators Offer Proven, Long Lasting Reliability



PAM MOTOR

- Multispeed, Squirrel Cage Induction Motor with a Single Winding Ideal for ID, FD, and PA Fan Applications
- Lighter, Smaller and More Efficient than a Two-Winding Motor fo
- Longer Rotor Life Due to Less Heating During Starting

AC Electric Motors

Power Savings at Reduced Loads







TECO W Westinghouse



2300/ 4160V; WP2 Enclosure

Ideal for H-Pump or Reciprocation Applications Suitable for Class 1, Div 2, Groups B, C & D; Temp Code T3C

Bi-directional, F1 and F2 Inverter Duty Design



DC MOTORS

- and Special Application Markets
- Resistance over Life of the Motor "Balanced Spring" Commutator to Assure Long Brush Life and
- Rugged Armature Featuring Keyless Fits
- Spherically-Seated, Self-Aligning, Split-Sleeve Bearings



Comparable Rating and Applications







5100 N. IH-35 • Round Rock, TX 7868 1-800-451-8798

www.tecowestinghouse.com

