Premium Efficient Motor & Drive Combination Packages from 1-800 HP for Constant Torque Applications

Inverter Duty Motors

ODP Rolled Steel or Cast Iron



MAX-E1®
Premium Efficient



Packages Include:

- Additional 5% Discount when Motor and Drive are Purchased on Same Order
 - 5 Year Warranty
 - Single Source Reliability



A510



EQ7

Variable Speed Drives

TECO Westinghouse

Select Any Combination of Motors & Drives Below

ODP NEMA Premium Efficient Motors 1-500 HP (460V) 1-125 HP (230V)

- 3600, 1800, or 1200 RPM
- Open Drip Proof (IP22 Rating)
- Construction:
 - Class F Insulation with Phenolic Alkyd Resin Varnish
 - Class B Temperature Rise
 - NEMA Design B Torques
 - 1045 Carbon Steel Shaft
 - Aluminum Die Cast Squirrel Cage Rotor Construction
- Speed Ranges: 20:1 VT, 10:1 CT
- Designed for 40°C Ambient Temperature and 3,300 ft Elevation
- Rolled Steel Frame (1-40 HP), Cast Iron Frame and End Brackets (1-500 HP)
- Rolled Steel Conduit Box
- Grounding Terminal Inside Main Box
- UL Recognized, CSA Approved, and CE Mark
- Oversized Main Conduit Box Rotatable in 90
 Degree Increments F1 Mounted. F2 Available
- Paint System: Phenolic Rust Proof Base Plus Polyurethane Top Coat
- Paint Color: Gray Munsell N5

A510 Heavy Duty Drive 1-200 HP (460V) 1-100 HP (230V)

- LCD Keypad that is Remotely Mountable
- Diagnostic Registers for Troubleshooting
- Enhanced Design for Smoother and Quieter Motor Operation
- Multiple Control Modes for General or Heavy Duty Applications.
- V/Hz, Open or Closed Loop Vector
- Built-in Modbus Communications
- Application Based Start-up Settings
- Built-in PLC as Standard
- High Starting Torque
- EMI Protection that complies with EN61800-3 with optional filter
- EMS Protection that Follows EN61800-3
- UL, cUL, and CE Approved

MAX-E1® Premium Efficient Motors 1-800 HP (460V) 1-125 HP (230V)

- 3600, 1800, or 1200 RPM
- Totally Enclosed, Fan Cooled (IP54 Rating;
 IP55 Rating at Frame Sizes 5000 and Larger)
- Construction:
 - Class F Insulation with Phenolic Alkyd Resin
 Varnish 2 Dips and Bakes
 - Class B Temperature Rise
 - NEMA Design B Torques
 - 1045 Carbon Steel Shaft
 - Aluminum Die Cast Squirrel Cage Rotor Construction
- Speed Ranges: 20:1 VT, 10:1 CT (3:1 CT at or above 350 HP)
- Designed for 40°C Ambient Temperature and 3,300 ft Elevation
- · Cast Iron Frame, End Brackets, and Fan Cover
- Cast Iron Conduit Box
- Grounding Terminal Inside Main Box
- UL Recognized, CSA Approved, and CE Mark
- Inverter Duty Magnet Wire Capable of Withstanding Voltage Spikes Up to 2,200 Volts
- Oversized Main Conduit Box Rotatable in 90 Degree Increments - F1 Mounted. F2 Available
- Paint System: Phenolic Rust Proof Base Plus Polyurethane Top Coat
- Paint Color: Gray Munsell N5

EQ7 Multi-Purpose Drive 1-800 HP (460V) 1-125 HP (230V)

- LED/LCD Keypad that can be Remotely Mounted
- Diagnostic Registers for Troubleshooting
- Enhanced Design for Smoother and Quieter Motor Operation
- Qty 9 Digital Inputs Plus Dedicated Safety Switch
- PID Control with Advanced Diagnostics and Sleep Mode
- Conformal Coating and Bus Bar Plating
- Built-in Modbus Communications
- Optional BACnet and Ethernet Communications
- EMI Protection that Complies with EN61800-3 with Optional Filter
- EMS Protection that Follows EN61800-3
- UL, cUL, and CE Approved

